

Material Safety Data Sheet

NanoSi-SP

1. Product and company identification

Product name : NanoSi-SP
Synonym : Silicon Powder
Material uses : Industrial use
CAS number : 7440-21-3
Manufacturer : REC Silicon Inc.

119140 Rick Jones Way Silver Bow, Montana 59750 United State of America

406-496-9877

Email: RECSiliconMSDS@recgroup.com

3322 Road N Northeast

Moses Lake, Washington 98837

United State of America

509-766-9299

Validation date : 12/05/2011.

Prepared by : Atrion Regulatory Services, Inc.

In case of emergency : CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

Physical state : Solid. [Powder.]

Color : Bluish-grey. Black. Brown.

Odor : Odorless.

Emergency overview

Signal word : WARNING!

Hazard statements : FLAMMABLE SOLID. MAY FORM EXPLOSIVE DUST-AIR MIXTURES. MAY CAUSE

RESPIRATORY TRACT. EYE AND SKIN IRRITATION. MAY CAUSE TARGET

ORGAN DAMAGE, BASED ON ANIMAL DATA.

Precautions : Keep away from heat, sparks and flame. Prevent dust accumulation. Avoid breathing

dust. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after

handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.Ingestion : No known significant effects or critical hazards.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

Potential chronic health effects

Chronic effects: May cause target organ damage, based on animal data. Repeated or prolonged

inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.

Hazards identification 2.

: No known significant effects or critical hazards. **Teratogenicity**

Developmental effects No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

: May cause damage to the following organs: upper respiratory tract, skin, eyes. **Target organs**

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

: No specific data. Ingestion

Skin : Adverse symptoms may include the following:

> irritation redness

: Adverse symptoms may include the following: **Eyes**

> irritation watering redness

Medical conditions aggravated by overexposure

: Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

Composition/information on ingredients 3.

Name	CAS number	%
Silicon	7440-21-3	99.99

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

First aid measures 4.

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water Eye contact for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention if symptoms occur.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes **Skin contact** while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if symptoms occur.

Move exposed person to fresh air. If not breathing, if breathing is irregular or if Inhalation respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms occur.

Ingestion Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical

attention if symptoms occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

No specific treatment. Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product

: Flammable solid. Fine dust clouds may form explosive mixtures with air. Runoff to sewer may create fire or explosion hazard. Evolves hydrogen on contact with water.

Extinguishing media

Suitable

Not suitable

- : Use dry chemical powder.
- : Do not use water jet.

Special exposure hazards

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: metal oxide/oxides hydrogen.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Use spark-proof tools and explosion-proof equipment. If emergency personnel are not present, sweep up small spillages, avoiding making dust and place in a suitable container for disposal. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Prevent dust accumulation. Fine dust clouds may form explosive mixtures with air. Use spark-proof tools and explosion-proof equipment. Avoid all possible sources of ignition (spark or flame). Vacuum or sweep up material and place in a designated, labeled waste container. References: NFPA 654, NEC Article 500. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Fine dust clouds may form explosive mixtures with air. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into

Handling and storage

contact with hot surfaces, sparks or other ignition sources. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits	
Silicon	OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 10 mg/m³ 8 hour(s). Form: Total dust OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust NIOSH REL (United States, 6/2009). TWA: 10 mg/m³ 10 hour(s). Form: Total	

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): Leather/ Vinyl gloves

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If operating conditions cause high dust concentrations to be produced, use dust goggles. Recommended: safety glasses with side-shields

Skin

 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

8. Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Solid. [Powder.]

Color : Bluish-grey. Black. Brown.

Odor : Odorless.

Molecular weight : 28.09 g/mole

Molecular formula : Si

Boiling/condensation point : 2355°C (4271°F) **Melting/freezing point** : 1410°C (2570°F)

Relative density : 2.33

Density : 0.3 to 1 g/cc **Viscosity** : Not available.

Solubility: Insoluble in the following materials: cold water and hot water.

Physical/chemical : Density: 0.3-1.0 gcc

properties comments

10. Stability and reactivity

Chemical stability

: The product is stable.

Conditions to avoid

: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials, acids, alkalis and moisture.

water

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Silicon	LD50 Oral	Rat	3160 mg/kg	-

Chronic toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silicon	Eyes - Mild irritant	Rabbit	-	-	-

Sensitizer

12/05/2011. **United States** 5/9

11. Toxicological information

Not available.

Carcinogenicity

Classification

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Not available.

Persistence/degradability

Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN3132	Water-reactive solid, flammable, n.o.s. (silicon)	4.3 (4.1)	II	NOCETOUS TO	Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 15 kg Cargo aircraft Quantity limitation: 50 kg

12/05/2011. United States 6/9

NanoSi-SP						
14. Transport information						
						Special provisions IB4, T3
IMDG Class	UN3132	WATER-REACTIVE SOLID, FLAMMABLE, N.O.S. (silicon)	4.3 (4.1)	II		Emergency schedules (EmS) F-G, S-N
IATA-DGR Class	UN3132	Water-reactive solid, flammable, n.o.s. (silicon)	4.3 (4.1)	II		Passenger and Cargo Aircraft Quantity limitation: 15 kg Packaging instructions: 483 Cargo Aircraft Only Quantity limitation: 50 kg Packaging instructions: 490 Limited Quantities - Passenger Aircraft Quantity limitation: 5 kg Packaging instructions: Y475

PG*: Packing group

Regulatory information 15.

HCS Classification

Flammable solid

Target organ effects

U.S. Federal regulations

: TSCA 8(a) IUR: Partial exemption

United States inventory (TSCA 8b): This material is listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Silicon

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

Silicon: Fire hazard, Immediate (acute) health hazard

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

Clean Air Act Section 112(b) Hazardous Air

: Not listed

Pollutants (HAPs)

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals)

SARA 313

Form R - Reporting requirements

Not applicable.

Supplier notification Not applicable.

State regulations

15. Regulatory information

Massachusetts : This material is listed.

New York : This material is not listed.

New Jersey : This material is listed.

Pennsylvania : This material is listed.

California Prop. 65

Not available.

United States inventory

(TSCA 8b)
Canada inventory

: This material is listed or exempted.

: This material is listed or exempted.

International regulations

International lists : Australia inventory (AICS): This material is listed or exempted.

China inventory (IECSC): This material is listed or exempted.

Japan inventory: This material is listed or exempted. **Korea inventory**: This material is listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted.

Philippines inventory (PICCS): This material is listed or exempted.

Chemical Weapons

Convention List Schedule I

Chemicals

: Not listed

Chemical Weapons
Convention List Schedule

Convention List Schedule

II Chemicals

: Not listed

Chemical Weapons
Convention List Schedule

III Chemicals


: Not listed

16. Other information

Label requirements

: FLAMMABLE SOLID. MAY FORM EXPLOSIVE DUST-AIR MIXTURES. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 12/05/2011.

Date of previous issue : No previous validation

Version :

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.